



Standart Features

- Steel construction body
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 4 guide ram
- Ram adjustment with ratchet system
- Mechanical disc overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap Groove
- Manuel Hand Pump
- Foot paddle
- Double hand control
- Single-continious-interrupted shot options
- PLC applied
- Electric counter
- Security PLC
- Compliance with CE directives
- Press Safety Valve
- Ram Cushioning Cylinders

Optional Features

- Electric and Timed Automatic Grease Lubrication System
- Speed Control Unit

	Value	Unit
Capacity	100	Ton
Throat Depth	270	mm
Table - Ram Distance	380	mm
Additional Table - Ram Distance	295	mm
Housing Width	440	mm
Ram Adjusment	75	mm
Press Width	1440	mm
Press Height	2540	mm
Press Depth	1540	mm
Table Hole Diameter	$\phi 175$	mm
Table Depth	540	mm
Table Width	750	mm
Die Tie Hole Diameter	$\phi 45$	mm
Ram Face Size	370 x 230	mm
Table Height From Floor	670	mm
Stroke	10-95	mm
Strok Per Minute	56	spm
Motor Power	11	kW
Motor Speed	1500	rpm
Approximate Weight	4050	kg

A3	ISO 128	HP_100_PK_AEP_MS	Technical Specifications		Page
TASARIM / DESIGNED	Taha Canat	08.05.2014			1/1
ÇİZEN / DRAWN	Taha Canat	16.12.2021			
KONTROL / CHECKED					

HICO MACHINERY AND ENGINEERING LTD. CO. reserves the right to make changes in dimensions without prior notice.